



Self-Contained Emergency KELUAR Sign

PEX-215F (WP) 2 x 8w (Fluorescent Tube)
(Weather-Proof Housing)



Specifications

Model	PEX-215F (2 x 8w) – WP (Weather Proof)
Mode	Sustained
Weight	2.5 Kgs
Battery	3 x 1.2V Ni-Cad
Housing	Polycarbonate Diffuser And Body (IP 65) Vinyl Stick-on letterings and pictogram
Charger	Constant Current
Mounting	Surface mounting direct to wall or ceiling
Dimension	665 mm (L) x 105 mm (W) x 172 mm (H)
Monitoring	Red LED indicating healthy supply and charging
Compliance	SIRIM MS 983, IP 65
Light Source	Mains on: 1 x 8W Fluorescent Lamp Mains off: 1 x 8W Fluorescent Lamp
Input Voltage	240 V +/- 10% 50/60 Hz
Recharge Period	16 - 24 Hours
Back Up Duration	3 Hours
Power Consumption	< 20 VA
Degree of Protection	IP - 65
Temperature	0 °C to 65 °C

For further enquires, please contact:

PNE SYSTEMS SDN. BHD. (263861 D)

No. 3, Jalan SS26/13,
Taman Mayang Jaya, 47301 Petaling Jaya,
Selangor Darul Ehsan, Malaysia.

Tel : 03-7803 7488 (Hunting)

Fax : 03-7803 8509

E-mail : pnesys@po.jaring.my